LEDLENSER



















LIFESTYLE PRODUCT CATALOG












Ledlenser believes that a simple beam of light can empower the world. It allows us to explore worlds, to discover wonders, to feel warmth and inspiration. Light allows us to go further than we ever imagined possible.

We each have the power to radiate positivity, to cast inspiration, and to ignite and illuminate meaningful change. The world is as bright as you make it.





CONTENT

LIFESTYLE



3 CONTENT

- 4-9 NEW PRODUCTS
 - 6 HF8R Core RGB NEW
- 8 P9R Core LEP NEW

10-23 FLASHLIGHTS

- 12 P2R Core
- 12 **P3 Core**
- 13 **P4 Core**
- 13 P4R Core
- 14 **P5 Core**
- 14 P5R Core
- 15 **P6 Core**
- 15 P6R Core
- 16 **P7 Core**
- 17 P7R Core
- 17 P9R Core LEP NEW
- 17 **P17R** Core
- 18 P6R Core QC
- 22 P6R Signature
- 22 P7R Signature
- 23 P18R Signature

24-27 KEYRING LAMPS

K4R

26 K6R

27 K6R Safety

28-33 KIDSLIGHTS



- 31 KIDLED2
- 31 KIDLED4R
- 32 KIDBEAM4
- 32 KIDCAMP6



34-39 XP-SERIES / X-SERIES

- XP30R
- X21R

40-55 HEADLAMPS



45 **HF6R Core**

45 HF8R Core

45HF8R Core RGB NEW



48 H5R Core

49 H7R Core

49 **H15R Core**

49 **H19R Core**

50 H19R Signature

54 **NEO1R**

55 **NEO3**

55 **NEO5R**

55 **NEO9R**

56-57 CLIPLIGHT

57 **CU2R**

58-63 LANTERNS

62 **ML4**

62ML4 Warm Light

63 **ML6**

63ML6 Warm Light

63ML6 Connect WL

64-69 PORTABLE ENERGY

66 **FLEX5**

66 FLEX10

68 **FLEX3**

68 **FLEX7**

70-73 ACCESSORIES

76-79 TECHNOLOGIES

80-81 ABOUT US

82-83WARRANTY + ISO

84-85 NOTES + CONTACT

NEW PRODUCTS







HF8R-CORE RGB

ADAPTIVEPOWERHOUSEFORHUNTINGANDFISHING


MULTICOLOR

The HF8R CoreRGBisidealforhuntersandanglers. Its innovative Adaptive Light Beam Technologyallows automatic dimming and focusing so you can be totally hands-free. Depending on your usecase, you can choose between an additional red, green or blue front light.

TRULY HANDS-FREE DIMS AND FOCUSES AUTOMATICALLY











PRESERVES NIGHT VISION - IDEAL FOR PREPARING YOUR GEAR AT NIGHT

DIGITAL ADVANCED

FOCUS SYSTEM

ADAPTIVE LIGHT BEAM



GREEN
ALMOST INVISIBLE TO SOME
ANIMALS – SUITABLE FOR WILDLIFE
WATCHING



BLUE
CAN MAKE LIQUIDS MORE
VISIBLE – HELPFUL WHEN
TRACKING PREY



- 01 Powerful headlamp with RGB front light
- 02 Automatic dimming and focusing thanks to our Adaptive Light Beam Technology – the system detects reflections and lighting conditions and automatically controls all light sources separately. This allows the HF8R to be used completely hands-free.
- **03 Powerful battery** can easily be recharged via Magnetic Charge System
- 04 Water and dustproof (IP68)
- **05** Lamp head tilts **steplessly**
- **06** Perfect light pattern for any range and virtually seamless focusing thanks to our **Digital Advanced Focus System**; optional manual operation via **Focus Wheel**
- **07** High-quality aluminum housing
- 08 Remote control and personalization via Ledlenser Connect App
- 09 Camouflage headband with detachable overhead strap

More information on page 47

P9R CORE LEP NEW

EXTREME

BEAM RANGE

True laser powerinyourhands!Thereisnoneedto decide between a highlyfocusedwhitelightwithanextreme beam range or a homogeneousilluminationatcloserange. Our newP9R Core LEPoffersbothandisidealforsearch and rescue teams, membersofthemaritimesectoraswell as hunters and anglers.

MAXIMUM BEAM RANGE: LED BECOMES LEP



Laser as a light source: Instead of using an LED, blue laser light is directed at a phosphor-coated plate and transformed into white light which then travels through two lenses, resulting in a white light that is highly focused and has an extreme range.



-;<-1000 lm1-⇒1300 m1-



- 01 Laser Excited Phosphor Technology creates a highly focused white light with an extreme beam range
- **02 White and red light** for homogeneous illumination at close range
- **03 Intuitive mode switch** for direct access to light functions
- **04 Hard-anodized housing material** for added protection against wear and corrosion, high dust and water protection (IP68)
- **05** Convenient charging of the battery via Magnetic Charge System

LEP COB COB

WHITE AND RED LIGHT FOR

CLOSE-RANGE ILLUMINATION

More information on page 17

FLASHLIGHTS











P-SERIES CORE





| 1x Power LED | 1x Power LED |
|---|---|
| Power / Mid Power / Low Power | Power / Mid Power / Low Power |
| 120 / 50 / 15 | 90 / 50 / 15 |
| 65 / 45 / 15 | 110 / 70 / 40 |
| 0.5 / 1 / 5 | 3 / 4 / 6 |
| 6000 - 7500 | 6000 - 7500 |
| 70 | 70 |
| | |
| 1x Li-ion Battery 3.7V mit Micro-USE | 31x Micro (AAA) Alkaline 1.5V |
| 0.74 / 200 | |
| IP54 | IP54 |
| Yes | No |
| 150 | |
| 2 | 2 |
| | |
| 103 | 96 20 |
| 15 | 42 / 1.5 |
| 36 / 1.3 | |
| | |
| | |
| | |
| | |
| | |
| • | • |
| Energy Saving | Rapid Focus |
| | |
| 502176 / 4058205020367 | 502597 / 4058205028462 |
| 1 Battery Set, Pocket Clip, Micro-USB Charging Cable | 1 Battery Set, Pocket Clip |
| | |
| 502248 Lamp Adapter Type A | 0337 Pouch Type D |
| 0337 Pouch Type D | 502248 Lamp Adapter Type A |
| 0380 USB Car Charger | |
| | Power / Mid Power / Low Power 120 / 50 / 15 65 / 45 / 15 0.5 / 1 / 5 6000 - 7500 70 1x Li-ion Battery 3.7V mit Micro-USE 0.74 / 200 IP54 Yes 150 2 103 15 36 / 1.3 Energy Saving Energy Saving 502176 / 4058205020367 1 Battery Set, Pocket Clip, Micro-USB Charging Cable 502248 Lamp Adapter Type A 0337 Pouch Type D |

| A PARTIE D | geable |
|-------------------------------|---|
| | PAP COPE |
| P4 CORE | P4R CORE |
| | |
| x Power LED | 1x Power LED |
| ower / Mid Power / Low Power | Power / Mid Power / Low Power |
| 20 / 60 / 15 | 200 / 90 / 15 |
| 0 / 55 / 25 | 90 / 60 / 15 |
| / 9 / 20 | 1.5 / 3 / 25 |
| 000 - 7500 | 6000 - 7500 |
| 0 | 70 |
| | |
| x Micro (AAA) Alkaline 1.5V | 1x Li-ion Battery Pack 3.7V |
| | 2.22 / 600 |
| 254 | IP54 |
| 0 | Yes |
| | 150 |
| | 2 |
| | |
| 46 | 150 |
| 5 | 15 |
| 8 / 2.0 | 55 / 1.9 |
| | |
| | |
| | |
| | |
| | |
| <u> </u> | |
| , | Energy Saving |
| | Liter gy Saving |
| 00500 / /05005000/00 | 500455 44050050000 |
| 02598 / 4058205028493 | 502177 / 4058205020398 |
| Battery Set, Pocket Clip | 1 Battery Set, Pocket Clip, Micro-USB Charging Cable |
| | |
| 02248 Lamp Adapter Type A | 502248 Lamp Adapter Type A |
| ozz ro zamp Adapter Type A | 0380 USB Car Charger |
| | 502271 USB Adapter |
| | 30227 1 03b Adaptol |



1-9 Information on page 84

P-SERIES CORE



reddot winner 2021







reddot winner 2021







| CORE | P | 5 | R | C | 0 | F | (|
|------|---|---|---|---|---|---|---|
|------|---|---|---|---|---|---|---|

| | P5 CORE | P5R CORE |
|--------------------------------|--------------------------------|--|
| LED | | |
| ← LED Configuration | 1x High Power LED | 1x High Power LED Boost / Power / Mid |
| □Ⅲ Light Functions | Power / Mid Power / Low Power | Power / Low Power (+ Position, Blink, S.O.S., Strobe) |
| -Ò- Luminous Flux1 (lm) | 150 / 60 / 15 | 500 / 350 / 130 / 15 |
| □→ Beam Distance1 (m) | 90 / 60 / 30 | 250 / 180 / 110 / 40 |
| Run Time1 (h) | 2.5 / 5 / 12 | - / 1 / 3.5 / 25 |
| Color Temperature (K) | 6000 - 7500 | 6000 - 7500 |
| R Color RenderingIndex(CRI) | 70 | 70 |
| BATTERY AND CASE | | |
| ■ Battery | 1x Mignon (AA) Alkaline 1.5V | 1x 14500 Li-ion Battery 3.7V |
| Battery Capacity2 (Wh / mAh) | | 2.77 / 750 |
| ○ IP Level | IP44 | IP68 |
| Rechargeable | No | Yes |
| Charging Time5 (min) | | 120 |
| □ Drop Height (m) | 2 | 2 |
| SIZE AND WEIGHT | | |
| ∠ Length – Defocused (mm) | 120 | 123 |
| Head Diameter (mm) | 26 | 29 |
| Weightincl.battery (g / oz) | 83 / 2.9 | 106 / 3.7 |
| TECHNOLOGY | | |
| SmartLight Technology | | • |
| Flex Sealing Technology | | • |
| Magnetic Charge System | | • |
| Temperature Control | | • |
| Advanced Focus System | • | • |
| More Features | Dual Power Source, Rapid Focus | Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode Emergency Light, Battery Indicator, Charge Indicator, Low Battery Warning |
| PACKAGING | | |
| Itemno. Box/GTIN | 502599 / 4058205028523 | 502178 / 4058205020428 |
| Content Box | 1 Battery Set, Lanyard | 1 Battery Set, Lanyard, Magnetic Charging Cable |
| OPTIONAL ACCESSORIES | | |
| | 502700 Lamp Adapter Type F | 502248 Lamp Adapter Type B |
| Further accessories on page 70 | 0337 Pouch Type D | 502259 Charging Station Type A |
| | | |



| IP54 | IP68 |
|------|------|
| No | Yes |
| | 300 |
| 2 | 2 |
| | |
| 117 | 151 |
| 22 | |

170 / 6.0

9.25 / 2500

| • |
|---|
| • |
| • |
| • |

130 / 4.6

| 3, 3, 1 | Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode |
|---------|--|
| | Emergency Light, Temperature Control |
| | System, Battery Indicator, Charge |
| | Indicator, Low Battery Warning |

| System, Battery Indicator, Charge Indicator, Low Battery Warning |
|--|
| |
| 502179 / 4058205020459 |
| 1 Battery Set, Lanyard, Magnetic Charging Cable |
| |
| 502250 Lamp Adapter Type C |
| |

⁹ Information on page 84



- predection (IP68)
- 02 Advanced Focus System - stepless focusing
- 03 Flex Sealing Technology – can be used for a short time underwater (including the focusing system) to a depth of one meter
- **04** Personalize the light functions via **Smart Light Technology**
- **05** Convenient and safe charging the battery thanks to the Magnetic Charge System
- 06 Constant Light constant luminous flux over a long period
- **07** Flicker-free constant light enables optimal and safe illumination

P-SERIES CORE














P7 CORE

| LED | |
|--------------------------------|-------------------------------|
| △ LED Configuration | 1x Power LED |
| Light Functions | Power / Mid Power / Low Power |
| -்C- Luminous Flux1 (lm) | 450 / 250 / 40 |
| ⊏ ⇒ Beam Distance1 (m) | 300 / 220 / 100 |
| 🕒 Run Time1 (h) | 1 / 2 / 25 |
| Color Temperature (K) | 6000 - 7500 |
| (CRI) | 70 |
| BATTERY AND CASE | |
| ■ Battery | 4x Micro (AAA) Alkaline 1.5V |
| Battery Capacity2 (Wh / mAh) | |
| Ф IP Level | IP54 |
| 🖒 Rechargeable | No |
| h Charging Time5 (min) | |
| <u>↓</u> Drop Height (m) | 1 |
| SIZE AND WEIGHT | |
| ✓ Length – Defocused (mm) | 130 |
| Head Diameter (mm) | 37 |
| Weightincl.Battery (g / oz) | 175 / 6.2 |
| TECHNOLOGY | |
| SmartLight Technology | |
| Flex Sealing Technology | |
| Magnetic Charge System | |
| Multi Core Optics | |
| Advanced Focus System | • |
| More Features | Energy Saving, Rapid Focus |
| | |
| | |
| | |
| PACKAGING | |
| Itemno. Box/GTIN | 502180 / 4058205020480 |
| Content Box | 1 Battery Set, Lanyard |
| OPTIONAL ACCESSORIES | |
| Further accessories on page 70 | |



502251 Lamp Adapter Type D

0042 Signal Cone 53 mm

1-9 Information on page 84

502251 Lamp Adapter Type D

P6R COR



- 01 Equipped with a Multicolor LED with white, red, green and blue light
- **02 Multicolor Strobe** colored flashes of light with irritating glare effect for emergencies
- **03 Easy Operation** the rotary switch enables quick color changes
- **04 Advanced Focus System –** stepless focusing



P6R CORE QC



| | | I OIL COILE &C |
|----------------|------------------------------|--|
| L | ED | |
| \bigcirc | LED Configuration Light | 1x Power LED Power / Mid |
| all | Functions (weißes Licht) | Power / Low Power 270 / 120 / |
| - <u>`</u> Ċ́- | Luminous Flux1 (lm) | 15 335 / 220 / 80 5 / 14 / 110 |
| | Beam Distance1 (m) | 6000 - 6500 80 (white light) |
| <u>(L)</u> | Run Time1 (h) | |
| Ŋκ | Color Temperature (K) | |
| (CRI) | Color RenderingIndex(CRI) | |
| В | SATTERY AND CASE | |
| | Battery | 1x Li-ion Battery 3.7V |
| - | Battery Capacity2 (Wh / mAh) | 9.25 / 2500 |
| ক্ | IP Level | IP54 |
| \$ | Rechargeable | Yes |
| Ō | Charging Time5 (min) | 300 |
| <u>7</u> | Drop Height (m) | 1.5 |
| S | SIZE AND WEIGHT | |
| <u></u> | Length – Defocused (mm) | 157 |
| \bigcirc | Head Diameter (mm) | 42 |
| g | Weightincl.Battery (g / oz) | 207 / 7.3 |
| T | ECHNOLOGY | |
| (3) | Rapid Focus | • |
| | Advanced Focus System | • |
| | More Features | Multicolor Strobe, Singlecolor Strobe |
| P | ACKAGING | |
| | Itemno. Box/GTIN | 502517 / 4058205026819 |
| | Content Box | 1 Battery Set, Lanyard, Micro-USB Charging Cable |
| C | PTIONAL ACCESSORIES | |
| | | 502251 Lamp Adapter Type D |
| Fui | ther accessories on page 70 | 502729 Remote Switch Type G |
| | | to the second se |

IN A DIFFERENT LIGHT LED Forensic analysis: liquids appear with higher contrast Maintain Wildlife watching: night vision ability green light is almost invisible to animals Ill Light Functions Power / Mid Power / Low Power Power / Mid Power / Low Power Power / Mid Power / Low Power -\(\hat{\}\)- \(\hat{\}\)- \(\h 220 / 75 / 15 35 / 10 / 5 300 / 190 / 80 50 / 30 / 15 L Run Time1 (h) 6 / 20 / 120 7 / 20 / 120 6 / 24 / 70

SEEING THE WORLD

P7R SIGNATURE

THE P-SERIES PREMIUM ILLUMINATION




















- 03 Additional red secondary light on the side of the housing,e. g. to maintain the night vision
- **04 Hard-anodized housing material** for additional protection against wear and corrosion
- 05 Extreme dust and water protection (IP68)
- **06 Flex Sealing Technology** can be used for a short time underwater (including the focusing system) to a depth of one meter
- **07** Personalize the light functions thanks to **Smart Light Technology**
- **08 Constant Light** consistent level of brightness over time
- 09 Integrated battery and charge status indicator



90 h1



1-9 Information on page 84

MAXIMUM PERFORMANCE, **STYLISH DESIGN**















P6R SIGNATURE

P7R SIGNATURE

| L | ED | | |
|------------------------|------------------------------|---|--|
| $\overline{\triangle}$ | LED Configuration | 1x Xtreme LED, (1x red LED) | 1x Xtreme LED, (1x red LED) |
| 411 | Light Functions | Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe, Red Ligh | Boost / Power / Mid Power / Low Power at)(+ Position, Blink, S.O.S., Strobe, Red Light |
| - <u>`</u> Ċ;- | beminous flux 1 (lm) | 1400 / 1100 / 450 / 15 | 2000 / 1200 / 500 / 15 |
| | Run Time1 (h) | 240 / 190 / 110 / 20 | 330 / 200 / 130 / 20 |
| <u>(C)</u> | Color Temperature (K) | - / 1.25 / 2.5 / 60 | - / 2 / 3.25 / 90 |
| Дк | | 6000 - 7500 | 6000 - 7500 |
| (CRI) | Color RenderingIndex(CRI) | 80 | 80 |
| | BATTERY AND CASE | | |
| | Battery | 1x 18650 Li-ion Battery 3.6V | 1x 21700 Li-ion Battery 3.7V |
| 111-11 | Battery Capacity2 (Wh / mAh) | 10.89 / 3000 | 17.76 / 4800 |
| ආ | IP Level | IP68 | IP68 |
| ٩ | Rechargeable | Yes | Yes |
| ð | Charging Time5 (min) | 225 | 270 |
| Ŷ | Drop Height (m) | 2 | 2 |
| S | SIZE AND WEIGHT | | |
| 7 | Length – Defocused (mm) | 151 | 158 |
| $\overline{\bigcirc}$ | Head Diameter (mm) | 35 | 35 |
| P | Weightincl.Battery (g / oz) | 170 / 6.0 | 202 / 7.1 |
| T | ECHNOLOGY | | |
| (1) | SmartLight Technology | • | • |
| | Flex Sealing Technology | • | • |
| <u></u> | Magnetic Charge System | • | • |
| | Multi-Core Optics | • | • |
| (4) | Advanced Focus System | • | • |
| | More Features | Red Alternate Light, Mode Switch, Emergency Light, Temperature Control, E Dimmable, Transportation Lock, Flicker-I free, Memory Function, Backup Mode, Emergency Light, Battery Indicator, Char- ge Indicator, Low Battery Warning | Dimmable, Transportation Lock, Flicker- free, Memory Function, Backup Mode, |
| | PACKAGING | | |
| | Itemno. Box/GTIN | 502189 / 4058205020756 | 502190 / 4058205020787 |
| | Content Box | 1 Set of Batteries, Leather Belt Pouch, Lanyard, Magnetic Charging Cable, Pocke Clip, USB Power Adapter, Wall Bracket | 1 Set of Batteries, Leather Belt Pouch, Lanyard, Magnetic Charging Cable, Pocket Clip, USB Power Adapter, Wall Bracket |



P18R SIGNATURE

| _ | | | | | _ | _ |
|----|----|-----|----|---|---|---|
| 3x | Χt | rer | ne | 1 | H | |

Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe) 4500 / 2600 / 1000 / 30

720 / 420 / 260 / 50

- / 2.5 / 4.5 / 70

6000 - 7200

70

1x Li-ion Battery Pack 11.1V

33.3 / 3000

IP54

Yes 330

171

637 / 22.5

X-Lens Technology, Rapid Focus, Dimmable, Transportation Lock, Flicker-free, Memory Function, Backup Mode, Emergency Light, Battery Indicator, Charge Indicator, Low Battery Warning

502191 / 4058205020817

1Set of Batteries, Lanyard, USB Power Adapter, Magnetic Charging Cable

P-SERIES SIGNATURE





KEY RING LIGHTS















K-SERIES











| | | K4R |
|----------------|------------------------------|---|
| | ED | |
| \Box | LED Configuration | 1x Power LED |
| 411 | Light Functions | / Power / Low Power |
| - <u>`</u> Ċ;- | Luminous Flux1 (lm) | 120 / 80 / 20 |
| \Box | Beam Distance1 (m) | 30 / 25 / 10 |
| <u>(L)</u> | RunTime (h) | - / 1 / 3.5 |
| В | ATTERY AND CASE | |
| | Battery | 1x Li-ion Battery 3.7V |
| III - I | Battery Capacity2 (Wh / mAh) | 0.67 / 180 |
| ٩ | Rechargeable | Yes |
| Ō | Charging Time5 (min) | 180 |
| ф | IP Level | IP2X |
| S | IZE AND WEIGHT | |
| <u></u> | Length (mm) | 52 |
| \bigcirc | Width (mm) | 25 |
| g | Weight incl.Battery (g / oz) | 20 / 0.7 |
| F | EATURES | |
| | | Transportation Lock, Battery Indicator, Charge Indicator |
| Р | ACKAGING | |
| | Item no. Box / Gray | Gray: 502574 / 4058205029117 |
| | Item no. Box / Rosé-Gold | Rose Gold: 502575 / 4058205029148 |
| | Content Box | Carabiner, Key Ring |



Carabiner, Key Ring





| K6 | R S | afe | ty |
|----|-----|-----|----|
|----|-----|-----|----|

Carabiner, Key Ring, Wrist Strap

| K6R | K6R Safety |
|--|---|
| | |
| 1x High Power LED | 1x High Power LED |
| Boost / Power / Low Power (+ red light) | Boost / Power / Low Power (+ Strobe) |
| 400 / 200 / 20 | 400 / 200 / 20 |
| 80 / 50 / 15 | 80 / 50 / 15 |
| - / 1.5 / 10 | - / 1.5 / 8 |
| | |
| 1x Li-ion Battery 3.7V | 1x Li-ion Battery 3.7V |
| 2 / 550 | 1.48 / 400 |
| Yes | Yes |
| 180 | 180 |
| IP2X | IP2X |
| | |
| 62 | 66 |
| 30 | 30 |
| 30 / 1.1 | 32 / 1.1 |
| | |
| Transportation Lock, Red Light, Battery Indicator, Charge Indicator | Transportation Lock, Shrill Alarm, Battery Indicator, Charge Indicator |
| | |
| Gray : 502577 / 4058205028318 | Safety Gray: 502580 / 4058205028370 |
| Rose Gold: 502578 / 4058205028622 | Rose Gold: 502581 / 4058205028721 |

KIDSLIGHTS



LEDLENSER





KIDSLIGHTS

LIGHT, FUN AND SAFETY

The Ledlenser KidsLights series lights specifically address the needs and requirements of children. They offer a wide range of uses, from the self-made cave to the safe way to school, a multitude of colorful light functions, quick and easy operation, and practical energy-saving features. And, most importantly, safety always comes first. For instance, glaring effects and the luminous flux are reduced and all headlamps come with safety head-bands which open automatically.



Versatile: white light, red light and blue light with optional flashing functions (red and blue)

Clever: Optics with reduced glaring for children's sensitive eyes

Energy-saving: automatic switch-off after 20 minutes (optional)



Practical: integrated metal clip for further attachment options without headband (e. g. on school satchel, backpack, clothing)



Safe: Pressure sensitive headband that releases automatically to prevent accidental injury

















| LED | | |
|---------------------------------|--|--|
| ☐ LED Configuration | 1x Power LED (White), 1x LED (Red), 1x LED (Blue) | 1x Power LED (White), 1x LED (Red), 1x LED (Blue) |
| Ⅲ Light Functions | | Power (White), Low Power (White), (Power e), (Red), Blink (Red), Power (Blue), Blink (Blue) Blink (Red / Blue)) |
| ்(- Luminous Flux1 (lm) | 40 / 5 | 40 / 5 |
| ⊐→ Beam Distance1 (m) | 9 / 2 | 9/2 |
| RunTime (h) | 1.5 / 20 | 2 / 18 |
| BATTERY AND CASE | | |
| ■ Battery | 1 x AAA Alkaline 1.5V | 1 x Li-ion 3.7V (intern) |
| Battery Capacity2 (Wh / mAh) | _ | 1.036/280 |
| ■ Rechargeable | No | Yes |
| Charging Time5 (min) | - | 60 |
| P IP Level | IPX4 | IP56 |
| SIZE AND WEIGHT | | |
| Durchmesser (mm) | 54 | 37 |
| og√ Weightincl.Battery (g / oz) | 35 / 1.2 | 25 / 0.9 |
| FEATURES | | |
| | White Light, Red Light, Blue Light, Automatic Switch-Off (optional), Safety Headband, Metal Clip for Mounting as Clip Light | White Light, Red Light, Blue Light, Automatic Switch-Off (optional), Safety Headband, Metal Clip for Mounting as Clip Light, Charge Indicator |
| PACKAGING (BOX) | | |
| Item no. / GTIN | 502537 (Green) / 4058205027038 | 502535 (Green) / 4058205026970 |
| Item no. / GTIN | 502538 (Purple) / 4058205027069 | 502536 (Purple) / 4058205027007 |
| Content Box | 1 Set of Batteries | Micro-USB Charging Cable |
| | | |

^{*} Caution: Not suitable for children under 36 months. Caution: Use under direct adult supervision.

¹⁻⁹ Information on page 84



KIDSLIGHTS







KIDBEAM4*


KIDCAMP6*


| LED | | |
|---|--|---|
| △ LED Configuration | 1x Power LED (White), 1x LED (Red), 1x LED (Blue), 1x LED (Gree | 1x Power LED (White), en)1x LED (Red), 1x LED (Blue), 1x LED (Gree |
| ull Light Functions | Power (White) / Low Power (White) (+ Power (Red), Power (Blue), Power (Green), Blink (Red und Blue)) | Power (White) / Low Power (White) (+ Power (Red), Power (Blue), Power (Green), Blink (Red, Blue und Green)) |
| -\(\overline{\chi}\)- Luminous Flux1 (lm) | 70 / 10 | 60 / 10 |
| ⇒ Beam Distance1 (m) | 12 / 5 | - / - |
| RunTime (h) | 4 / 18 | 8 / 40 |
| BATTERY AND CASE | | |
| | 2 x AAA Alkaline 1.5V | 3 x AAA Alkaline 1.5V |
| (a) Battery Capacity2 (Wh / mAh) | - | - |
| Rechargeable | No | No |
| Љ Charging Time5 (min) | - | - |
| □ IP Level | IP44 | IP44 |
| SIZE AND WEIGHT | | |
| O Durchmesser (mm) | 35 | 75 |
| Weightincl.Battery (g / oz) | 72 / 2.5 | 95 / 3.4 |
| FEATURES | | |
| | White Light, Red Light, Blue Light, Green Light, Automatic Switch-Off (optional), Clip | White Light, Red Light, Blue Light, Green Light, Automatic Switch-Off (optional), Fold-Out Hook for Hanging Up the Light |
| PACKAGING (BOX) | | |
| Item no. / GTIN | 502754 (Green) / 4058205030861 | 502753 (Green) / 4058205030847 |
| Item no. / GTIN | 502789 (Purple) / 4058205031653 | 502786 (Purple) / 4058205031561 |
| Content Box | 1 set of batteries | 1 set of batteries |

^{*} Caution: Not suitable for children under 36 months. Caution: Use under direct adult supervision.

¹⁻⁹ Information on page 84







KIDBEAM4 AAA Alkaline Batteries











Exploring with your first own flashlight: The robust Kidbeam4 lights up in four different colors and impresses with practical, child-specific features such as the integrated clip or the automatic switch-off function.

KIDCAMP6 AAA Alkaline Batteries













For cozy evenings of playing or reading: The Kidcamp6 provides the right mood and lights up in four different colors. It can be mounted in various ways thanks to the foldout hook, e. g. in a tent or caravan.


XP-SERIES / X-SERIES: LIGHT FOR EXTREME NEEDS





ULTIMATE LIGHT PERFORMANCE MADE IN GERMANY





04



01 – High-end portable searchlight with up to 32,000 lumens1 **02** - Extreme Search Beam - 30 powerful automotive LEDs combined with unique optics for extreme long-range vision without glare at close

- **OangActive Cooling Technology** powerful fan for maximum light output over a long period of time
- **04** AMPShare powered by Bosch battery with fast charging function
- **05** Compact dimensions and perfect weight distribution for optimal handling and single-handed operation
- **06** Remote control with up to 200 m range
- **07** Extremely robust due to protective elements and robust front glass
- **08** Screw thread for tripod mounting
- **09** Made in Germany development and production in Germany according to highest quality standards



- O1 Extreme light output up to 800 meters1 beam distance with up to 5000 lumens1 thanks to seven Xtreme LEDs
 O2 X-Lens Technology precise synchronization of the bundles of rays from several reflector lenses to form an extre-
- les of rays from several reflector lenses to form an extremely homogeneous, stage-like floodlight or a very sharply focused high beam
- **03 Advanced Focus System** stepless focusing
- **04** High-quality battery system **Safety Ytrion Cell** over 5000 charging cycles without significant loss of capacity
- **05** Quick to hand convenient charging with the **Floating Charge System**
- **06 Great ease of use** 7 light functions, 4 light programs, 2 energy modes, and 1 multi-function switch



EXTREME POWER RECHARGEABLE & MULTIFUNCTIONAL

| LE | D | |
|--------------------|-------------------------------|--|
| | ED Configuration | 7x Xtreme LED |
| all L | ight Functions | Boost / Power / Low Power (+ Blink, S.O.S., Strobe, Position) |
| -\\(\c)\- | uminous Flux1 (lm) | 5000 / 3500 / 200 |
| ⊐⇒ E | Beam Distance1 (m) | 800 / 700 / 150 |
| <u></u> F | Run Time1 (h) | - / 5 / 40 |
| ВА | TTERY AND CASE | |
| E | Battery | 1x LiFePO4 Battery Pack 9.6V |
| E | Battery Capacity2 (Wh / mAh) | 48 / 5000 |
| ြုံ F | Rechargeable | Yes |
| | Charging Time5 (min) | 210 |
| တ္ ။ | P Level | IP54 |
| SIZ | ZE AND WEIGHT | |
| _7 L | ength – defocused (mm) | 405 |
| | Head diameter (mm) | 95 |
| <mark>∕g\ V</mark> | Veight incl. Battery (g / oz) | 1315 / 45.9 |
| TE | CHNOLOGY | |
| 1 S | Smart Light Technology | • |
| 6 F | Rapid Focus | • |
| F | Floating Charge System | • |
| A | Advanced Focus System | • |
| ⊗ x | (-Lens Technology | • |
| ₩ E | Emergency Light | • |
| Ø 9 | Safety Ytrion Cell | • |
| ● T | emperature Control | • |
| N | More Features | Energy Saving, Constant Light, Charge Indicator, Battery Indicator, Dimmable, Transportation Lock |
| PΑ | CKAGING | |
| li | tem no. Carrying Case / GTIN | 501967 / 4058205015394 |
| C | Contents | 1 Battery Set, Floating Charge System, Assembly Material, Power Supply Unit, Roll Protection, Tripod Holder, Carrying Strap, Case |
| 0P | TIONAL ACCESSORIES | |
| | | 0386 Car Charger |





HEADLAMPS

















introduces its first hands-free headlamp. Why break your flowat work when your headlamp will adjust automatically or transition seamlessly, while providing you with the perfect light pattern. Without a battery box at the back of your head or an additional cable at the headband, you will be more











TRULY HANDS-FREE DIMS AND FOCUSES AUTOMATICALLY



-><-><-1600 lm1-≥⇒ 210 m1 -≥> 90 h1 -

- **01** Powerful headlamp with additional red front light
- 02 Automatic dimming and focusing thanks to our Adaptive Light Beam Technology – the system detects reflections and lighting conditions and automatically controls all light sources separately. This allows the HF8R to be used completely hands-free.
- **03 Powerful battery** can easily be recharged via Magnetic Charge System
- **04** Water and dustproof (IP68)

LEDLENSER

- **05** Lamp head tilts **steplessly**
- 06 Perfect light pattern for any range and virtually seamless focusing thanks to our <u>Digital Advanced Focus System</u>; optional manual operation via <u>Focus Wheel</u>
- **07** High-quality aluminum housing
- **08** Remote control via **Ledlenser Connect App** (upgrade with additional features available)



-HF-SERIES

























HF8R CORE



| 2x Xtreme LED, 1x High Power LED, 1x | 3x Xtreme LED, 1x High Power LED, 1x Red | 3x Xtreme LED, 1x High Power LED, 1x RGB LED |
|--|--|--|
| Red LED | LED | |
| Boost / Power / Mid Power / Low Power (+ Red Light) | Boost / Power / Mid Power / Low Power (+ Red Light) (+S.O.S., Alpine distress signal via App) | Boost / Power / Mid Power / Low Power (+ RGB Light) (+S.O.S., Alpine distress signal via App) |
| 800 / 500 / 250 / 20 | 1600 / 900 / 300 / 20 | 1600 / 900 / 300 / 20 |
| 160 / 140 / 80 / 25 | 210 / 200 / 100 / 25 | 210 / 200 / 100 / 25 |
| -/3/6/60 | - / 3.5 / 10 / 90 | - / 3,5 / 10 / 90 |
| 5200 – 6200 | 5200 – 6200 | 5200 – 6200 |
| 70 | 70 | 70 |
| | | |
| 1x Li-ion Battery Pack 3.7V | 1x Li-ion Battery Pack 3.7V | 1x Li-ion Battery Pack 3.7V |
| 7.4 / 2000 | 13.7 / 3700 | 13.7 / 3700 |
| IP68 | IP68 | IP68 |
| Yes | Yes | Yes |
| 225 | 270 | 270 |
| 2 | 2 | 2 |
| | | |
| 126 / 4.44 | 194 / 6.84 | 194 / 6.84 |
| | | |
| | • | • |
| • | • | • |
| • | • | • |
| • | • | • |
| • | • | • |
| Memory Function, Transportation Lock, Backup Mode, Aluminum housing, Battery Indicator, Charge Indicator, Low Battery Warning | | RGB Light, Bluetooth®, Transportsicherung, ,Memory Function, Backup Mode, Aluminium gehäuse, Emergency Light, Battery Indicato Charge Indicator, Low Battery Warning, Dim mable, Remote control and personalisation via Ledlenser Connect App |
| | | |
| 502796 Black / 4058205031837 | 502801 Black / 4058205031943 | 503089 Camouflage / 4058205036634 |
| 502966 Blue / 4058205034319 | - | |
| 502967 Red / 4058205034340 | - | - |
| 502797 White / 4058205031851 | _ | |
| Comfort Pad, Connect Adapter, Magnetic Charging Cable (USB-C) | Comfort Pad, Connect Adapter, Magnetic Charging Cable (USB-C), removable Overhead Strap | Comfort Pad, Connect Adapter, Magnetic Charging Cable (USB-C), removable Overhead Strap |

| | | HF4R CORE |
|----------------|-------------------------------|---|
| L | ED | |
| \triangle | LED Configuration | 2x High Power LED, 1x Red LED |
| u | Light Functions | Boost / Power / Mid Power / Low Power (+ Red Light) |
| <u>-\̈́\</u> - | Luminous Flux1 (lm) | 500 / 300 / 120 / 20 |
| ⇒ | Beam Distance1 (m) | 130 / 100 / 60 / 15 |
| <u>(b</u> | Run Time1 (h) | - / 2.5 / 5 / 35 |
| Įκ | Color Temperature (K) | 5200 – 6200 |
| (CRI) | Color RenderingIndex(CRI) | 70 |
| В | ATTERY AND CASE | |
| | Battery | 1x Li-ion Battery Pack 3.7V |
| <u> </u> | Battery Capacity2 (Wh / mAh) | 3.7 / 1000 |
| ထု | IP Level | |
| Ŷ | Rechargeable | Yes |
| <u> </u> | Charging Time5 (min) | 180 |
| <u>↓</u> | Drop Height (m) | 2 |
| V | /EIGHT | |
| ĝ | Weightincl.Battery (g / oz) | 72 / 2.54 |
| T | ECHNOLOGIE | |
| | Adaptive Light Beam | |
| | Digital Advanced Focus System | |
| <u></u> | Magnetic Charge System | • |
| | Temperature Control System | • |
| 1 | Cooling Technology | |
| | More Features | Fusion Beam, Transportation Lock, Memor Function, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning |
| Р | ACKAGING | |
| | Item no. Box / GTIN | 502790 Black / 4058205031684 |
| | Item no. Box / GTIN | 502791 Blue / 4058205031707 |
| | Item no. Box / GTIN | 502792 Red / 4058205031738 |
| | | Connect Adapter, Magnetic Charging Cable |

Connect Adapter, Magnetic Charging Cable (USB-C) Content Box Charging Cable (USB-C) removable Overhead Strap removable Overhead Strap 1-9 Information on page 84 Optional accessories on page 72













- **01** Intuitive operation and stepless dimming thanks to the wheel switch on the lamp head
- **02** Strong dust and water predection (IP67)
- 03 Stepless swivel mechanism for vertical alignment of the light cone
- **04 Advanced Focus System** stepless focusing
- **05** Convenient and safe charging of the battery thanks to the Magnetic Charge System
- 06 Integrated battery and charge status indicator
- **07 Ledlenser Connecting System** one interface for many accessories



-> 1000 lm1 ⇒ 250 m1

65 h1

THE H-SERIES



-H-SERIES CORE





| H5 CORE | |
|---------|--|
|---------|--|

| | no core | HOR CURE |
|------------------------------------|---|--|
| LED | | |
| LED Configuration | 1x High Power LED | 1x High Power LED |
| IIII Light Functions | Boost / Power / Low Power | Boost / Power / Low Power |
| -\(\dagger'-\) Luminous Flux1 (lm) | 350 / 200 / 15 | 500 / 300 / 15 |
| □ → Beam Distance1 (m) | 160 / 120 / 30 | 200 / 150 / 30 |
| Run Time1 (h) | - / 2 / 20 | - / 2 / 50 |
| [K Color Temperature (K) | 6000 - 7500 | 6000 - 7500 |
| © Color RenderingIndex(CRI) | 70 | 70 |
| BATTERY AND CASE | | |
| | 2x Mignon (AA) Alkaline 1.5V | 1x Li-ion Battery Pack 3.7V |
| Battery Capacity2 (Wh / mAh) | - | 6.66 / 1800 |
| 다 IP Level | IP67 | IP67 |
| Rechargeable | No | Yes |
| h Charging Time5 (min) | - | 210 |
| □ Drop Height (m) | 1.5 | 1.5 |
| SIZE AND WEIGHT | | |
| Head Diameter (mm) | 32 | 32 |
| (g / oz) | 178 / 6.3 | 167 / 5.9 |
| TECHNOLOGY | | |
| Multi-Core Optics | | |
| Flex Sealing Technology | • | • |
| Magnetic Charge System | | • |
| Fusion Beam | | |
| Advanced Focus System | • | • |
| More Features | Cooling Technology, Dimmable, Transportation Lock, Energy Saving | Cooling Technology, Temperature Control, Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Battery Indica- tor, Charge Indicator, Low Battery Warning, Constant Light |
| PACKAGING | | |
| Itemno. Box/GTIN | 502193 / 4058205020848 | 502121 / 4058205020879 |
| Content Box | 1 Set of Batteries | 1 Set of Batteries, Magnetic Charging Cable |
| OPTIONAL ACCESSORIES | 5 | |
| Further accessories on page 72 | 502451 Transp. Silicone Headband | 502256 Universal Mounting Bracket |
| | | |









R CORE H15R CORE


| 2 | H19R | CORE |
|---|-------------|------|
|---|-------------|------|

| TIT IN COINE | THOR SOILE | TIT / IX GOINE |
|---|---|--|
| | | |
| 1x Xtreme LED | 1x Xtreme LED | 2x Xtreme LED |
| Boost / Power / Low Power | Boost / Power / Low Power | Boost / Power / Mid Power / Low Power |
| 1000 / 600 / 15 | 2500 / 1000 / 20 | 3500 / 1600 / 800 / 200 |
| 250 / 200 / 25 | 250 / 170 / 20 | 300 / 230 / 150 / 80 |
| - / 4 / 65 | - / 5 / 80 | - / 4 / 7 / 20 |
| 6000 – 7500 | 6000 – 7500 | 6000 – 7500 |
| 70 | 70 | 70 |
| | | |
| 1x 21700 Li-ion Battery 3.7V | 1x Li-ion Battery Pack 7.4V | 1x Li-ion Battery Pack 7.4V |
| 17.76 / 4800 | 35.52 / 4800 | 35.52 / 4800 |
| IP67 | IP67 | IP68 |
| Yes | Yes | Yes |
| 210 | 330 | 330 |
| 1.5 | 1.5 | 1.5 |
| | | |
| 41 | 47 | 68 |
| 259 / 9.1 | 380 / 13.4 | 374 / 13.2 |
| | | |
| | | |
| • | • | |
| • | • | • |
| | | • |
| • | • | |
| Cooling Technology, Temperature Control, Dimmable, Transportation Lock, Flicker- free, Memory Mode, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning, Constant Light | Cooling Technology, Temperature Control, Dimmable, Transportation Lock, Flicker- free, Memory Mode, Backup Mode, Battery p Indicator, Charge Indicator, Low Battery Warning, Constant Light | Temperature Control, Cooling Technology, Optisense Technology, Dimmable, Trans- portation Lock, Flicker-free, Memory Mode, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning, Constant Light, Red Light |
| | | |
| 502122 / 4058205020909 | 502123 / 4058205020930 | 502124 / 4058205020961 |
| 1 Set of Batteries, Magnetic Charging Cable | 1 Set of Batteries, Magnetic Charging Cable | 1 Set of Batteries, Magnetic Charging Cable |
| | | |
| 502262 21700 Li-Ion Recharge. Battery | 502253 Belt Clip Type A | 502256 Universal Mounting Bracket |
| | | |

¹⁻⁹ Information on page 84









- **01 Fusion Beam** individually adjustable flood and spotlight for a unique light image with perfect illumination
- **02 Multi-Core Optics** homogeneous light image thanks to special faceting of the lens
- **03 Ledlenser Connect App** and **Bluetooth® remote control** enable personalization and remote control of the light functions
- **04 Optisense Technology** automatic adaptation to the light conditions thanks to the integrated sensor
- 05 Extreme Dust and Water Protection (IP68) 06 Additional Red Light to maintain night vision 07 Stepless Swivel Mechanism for vertical alignment of the light cone 08 Ledlenser Connecting System one interface for many
 - accessory parts
- 09 Additional Content
- 10 Reflective Headband






| | TIT/IL SIGNATORE |
|--------------------------------------|--|
| LED | |
| | 2x Xtreme LED |
| Ill Light Functions | Boost / Power / Mid Power / Low Power (+ Strobe, Positon, SOS, Blink, Red Light) |
| -\(\hat{\chi}\)- Luminous Flux1 (lm) | 4000 / 1800 / 800 / 200 |
| □ Beam Distance1 (m) | 330 / 250 / 150 / 80 |
| Run Time1 (h) | - / 3.5 / 7 / 20 |
| Color Temperature (K) | 6500 |
| © Color RenderingIndex(CRI) | 80 |
| BATTERY AND CASE | |
| Battery | 1x Li-ion Akkupack 7.4V |
| Battery Capacity2 (Wh / mAh) | 35.52 / 4800 |
| P Level | IP68 |
| Rechargeable | Ja |
| Charging Time5 (min) | 330 |
| □ Drop Height (m) | 1.5 |
| SIZE AND WEIGHT | |
| Head Diameter (mm) | 68 |
| Weightincl.Battery (g / oz) | 374 / 13.2 |
| TECHNOLOGY | |
| tusion Beam | • |
| ■ Magnetic Charge System | • |
| Femperature Control | • |
| More Features | Mutli-Core Optics, Red Light, Optisense, Coolin Technology, Emergency Light, Bluetooth®8, Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Battery Indicato Charge Indicator, Low Battery Warning, Constant Light |
| PACKAGING | |
| Item no. Box / GTIN | 502198 / 4058205021111 |
| Content Soft Case | Bluetooth®8 remote control, 1 Set of Batteries, Helmet Clips, Adapter for GoPro, Helmet Holder, Hook-and-Loop straps, Ad esive Pads, Magnetic Charging Cable, Tripod Holder, USB Power Adapter, Universal Holder, Extension Cable, Adhesive Pads |
| OPTIONAL ACCESSORIES | |
| | |


More Accessories on page 74



¹⁻⁹ Information on page 84

502310 2x 21700 Li-lon Recharge. Battery











ULTRALIGHT AND VERSATILE



Additional red light as a signal light and to maintain charging via Magnetic night vision capability



Quick and easy battery Charge System with status LED



Tilting lamp head for individual adjustment of the light cone

BRIGHT ALLROUNDER FOR SPORTY MISSIONS



Perfect light pattern for fast-moving activities with combined close and long distance light



Tilting lamp head for light cone



Minimalist, ergonomic design individual adjustment of the with cable tunnel for perfect fit and wearing; 360° visibility thanks to red flashing rear light; easy operation with three

COMPACT POWER FOR AMBITIOUS ATHLETES



Perfect light pattern for fast-moving activities with combined close and long distance light



360° visibility thanks to red flashing rear light and individual adjustment of reflective headband; quick the light cone and easy battery charging via Magnetic Charge System with status LED



Tilting lamp head for

THE PERFECT LIGHT FOR TRAIL RUNNERS



Extremely powerful trail running headlamp with outstanding light image; multiple light sources perfectly illuminate near and far in every situation



Extremely powerful, replaceable battery pack; rechargeable via Magnetic Charge System with status LED



Ergonomic design with removable overhead strap for perfect fit and wearing comfort during outdoor activities; included chest belt as additional attachment option

¹⁻⁹ Information on page 84



NEO-SERIES













NE01R

| LLD | |
|---------------------------------------|---------------------------|
| ☐ LED Configuration | 1x High Power LED |
| | Boost / Power / Low Power |
| - - - - - - - - - - - - - | 250 / 150 / 20 |
| □ Beam Distance1 (m) | 80 / 50 / 15 |
| © RunTime (h) | - / 3 / 15 |

| B | BATTERY AND CASE | |
|-------------|------------------------------|------------------------------|
| | Battery | 1x Li-ion Battery Pack 3.7 V |
| Ⅲ ▶1 | Battery Capacity2 (Wh / mAh) | 2.7 / 730 |
| Φ | Rechargeable | Yes |
| Ō | Charging Time5 (min) | 180 |
| <u>م</u> | IP Level | IP67 |
| | HZE AND WEIGHT | |

48

39 / 1.4

| | S | lΖΕ | AND | WEIGHI | |
|--|---|-----|-----|--------|--|
|--|---|-----|-----|--------|--|

Head Diameter (mm)

Weightincl.Battery (g / oz)

TECHNOLOGY

Fusion Beam

Magnetic Charge System

Temperature Control

More Features

Low Battery Warning, Battery Indicator, Charge Indicator, Red Light, Transportation Lock, Backup Mode

| Content Box | Magnetic Charging Cable |
|---------------------|--|
| Item no. Box / GTIN | 502712 Black / 4058205029957 |
| Item no. Box / GTIN | 502720 White/Lime / 4058205030168 |
| Item no. Box / GTIN | 502713 Blue / 4058205029971 |
| PACKAGING | |


OPTIONAL ACCESSORIES

Further accessories on page 72

0332 Pouch Type H



CLIPLIGHT CU2R





The CU2Rcanbeeasily used as a **BACKLIGHTFOR MANY** headlamps for example

for example HF-Series (p. 9) or NEO1R (p. 54)









CU2R

| LEU | |
|---|---|
| △ LED Configuration | 1x Power LED (White), 2x LED (Red) |
| 때에 Light Functions | Power (White), Low Power (White), (+ Power (Red), Blink (White), Blink (Red)) |
| -\:\rac{\dagger}{-} Luminous Flux1 (lm) | 40 / 5 |
| □ Beam Distance1 (m) | 9 / 2 |
| Run Time1 (h) | 2 / 18 |

| BATTERY AND CASE | |
|------------------------------|----------------------------|
| Battery | 1 x Li-ion 3.7V (internal) |
| Battery Capacity2 (Wh / mAh) | 1036 / 280 |
| (Rechargeable | Yes |
| h Charging Time5 (min) | 60 |
| ্ৰ IP Level | IPX4 |

| (Rechargeable | 162 |
|-------------------------------|---|
| Ĉ Charging Time5 (min) | 60 |
| ্ৰ IP Level | IPX4 |
| SIZE AND WEIGHT | |
| Diameter (mm) | 37 |
| Weight incl. Battery (g / oz) | 25 / 0.9 |
| FEATURES | |
| | Additional White and Red Flashing Light, Metal Clip for Attachment as Clip Light, Transportation Lock, Wrist Strap |


PACKAGING (BOX)
Item no. / GTIN

Content Box

Micro-USB Charging Cable, Wrist Strap

CU2R is your trusted light partner that provides extra everyday safety in dim conditions and beyond – whether it's on a walk with the dog, on an evening run during rush hour or in everyday life as a rear light on clothing or backpack.

- 01 Compact, lightweight and versatile signal light with reflective wristband to increase safety in the dark
- 02 One white LED and two extra bright red LEDs offering two modes (power, blink)
- 03 Intuitive operation with two separate switches for white light and red light
- 04 Elastic strap with hook-and-loop closure and metal clip for quick and flexible attachment, e. g. on upper arm, clothing or backpack



1-9 Information on page 84

502730 / 4058205030366

OUTDOOR LANTERNS













ML6 CONNECT WL Egg.



GLARE-FREE 360° ILLUMINATION WITH REMOTE CONTROL







LEDLENSER







02 – Ledlenser Connect App and wireless Bluetooth® remote control enable personalization and remote control of the light functions

- 03 Infinitely dimmable via three-way switch
- 04 Powerbank function with USB connection for charging electronic devices
- 05 Red light to maintain night vision ability
- **06** Rubber hook for hanging the light, integrated magnet for mounting it on metal surfaces, and a removable stand with a built-in metal hook that can be flipped out to provide more light mounting options
- **07** Convenient and safe charging via
 - Magnetic Charge System

08 – Integrated battery and charge status indicator



1-9 Information on page 84

03 | 08

ML-SERIES









502126 Flex3 Powerbank











| LED | | |
|--------------------------------------|--|--|
| △ LED Configuration | 9x Power LED, 9x LED Rot | 9x Power LED, 9x LED Rot |
| ៕ Ight Functions | Boost / Power / Mid Power / Low Power (+ Blink, alle Light Functions auch in Rot) | Boost / Power / Mid Power / Low Power (+ Blink, alle Light Functions auch in Rot) |
| -\(\hat{\tau}\)- Luminous Flux1 (lm) | 300 / 150 / 50 / 5 | 300 / 150 / 50 / 5 |
| ☐→ Beam Distance1 (m) | - | - |
| RunTime (h) | - / 2.5 / 8 / 45 | - / 2.2 / 7 / 40 |
| BATTERY AND CASE | | |
| Battery | 1x 14500 Li-ion Battery 3.7V | 1x 14500 Li-ion Battery 3.7V |
| Battery Capacity2 (Wh / mAh) | 2.77 / 750 | 2.77 / 750 |
| Rechargeable | Yes | Yes |
| h Charging Time5 (min) | 150 | 150 |
| O IP Level | IP66 | IP66 |
| SIZE AND WEIGHT | | |
| Diameter (mm) | 34.5 | 34.5 |
| Height (mm) | 97 | 97 |
| (g / oz) | 71 / 2.5 | 71 / 2.5 |
| TECHNOLOGY | | |
| MicroPrism Technology | • | • |
| Temperature Control | • | • |
| Powerbank Function | | |
| Magnetic Charge System | • | • |
| Dual Power Source | • | • |
| More Features | Low Battery Warning, Charge Indicator, Battery Indicator, Transportation Lock, Red Light | Low Battery Warning, Charge Indicator, Battery Indicator, Transportation Lock, Red Light |
| PACKAGING | | |
| Itemno. Window Box / GTIN | 502053 / 4058205017886 | 502231 / 4058205022125 |
| Content Box | 1 Set of Batteries, Magnetic Charging Cable | 1 Set of Batteries, Magnetic Charging Cable |
| OPTIONAL ACCESSORIES | | |
| Further accessories on page 72 | 502271 USB Adapter 2.4A | 502271 USB Adapter 2.4A |
| | | |

| ML6 | ML6 Warm Light | ML6 Connect W |
|-----|----------------|---------------|
|-----|----------------|---------------|

| = • | | |
|---|---|---|
| | | |
| 18x Power LED, 6x LED Rot | 18x Power LED, 6x LED Rot | 18x Power LED, 6x LED Rot |
| Boost / Power / Low Power (+ Blink, Pulse, S.O.S., Strobe, all functions also in red) | Boost / Power / Low Power (+ Blink, Pulse, S.O.S., Strobe, all functions also in red) | Boost / Power / Mid Power / Low Power (+ Blink, Pulse, Position, Strobe, S.O.S. Alpine emergency signal, all functions also in red) |
| 750 / 550 / 5 | 750 / 550 / 5 | 750 / 550 / 100 / 5 |
| | - | - |
| - / 4 / 240 | - / 3.5 / 200 | - / 3.5 / 12 / 180 |
| | | |
| 1x 18650 Li-ion Battery 3.6V | 1x 18650 Li-ion Battery 3.6V | 1x 18650 Li-ion Battery 3.6V |
| 10,89 / 3000 | 10.89 / 3000 | 10.89 / 3000 |
| Yes | Yes | Yes |
| 300 | 300 | 300 |
| IP66 | IP66 | IP66 |
| | | |
| 42 | 42 | 45 |
| 178 | 178 | 178 |
| 280 / 9.9 | 280 / 9.9 | 260 / 9.2 |
| | | |
| • | • | • |
| • | • | • |
| • | • | • |
| | | • |
| | | |
| Low Battery Warning, Charge Indicator, Battery Indicator, Dimmable, Transporta- tion Lock, Red Light, Memory Mode | Low Battery Warning, Charge Indicator, Battery Indicator, Dimmable, Transporta- tion Lock, Red Light, Memory Mode | Low Battery Warning, Charge Indicator, Battery Indicator, Dimmable, Transporta- tion Lock, Red Light, Bluetooth®, Memory Mode, Emergency Light |
| | | |
| 500929 / 4058205011259 | 502084 / 4058205017916 | 502201 / 4058205021203 |
| 1 Set of Batterie, Stand, Transport Bag, Micro-USB Cable | 1 Set of Batterie, Stand, Transport Bag, Micro-USB Cable | 1 Set of Batterie, Stand, Transport Bag, Magnetic Charging Cable |
| | | |
| L | Lange 1 1 1 1 1 1 1 1 1 | |

502126 Flex3 Powerbank

¹⁻⁹ Information on page 84

502126 Flex3 Powerbank

PORTABLE ENERGY FLEX-SERIES







FLEX-SERIES: THE FUTURE OF PORTABLE ENERGY



| | | 2170 | \mathbf{n} | TTFR | IEC |
|-----|-----|---------|--------------|------|-------|
| 1 1 | ruk | / I / I | JU DA | LIER | IES . |

FI FX5

FI FX10

| ☐ FOR 21700 BATTERIES | FLEXO | FLEXIU |
|------------------------------|--|---|
| TECHNICAL SPECS | Powerbank+ | Powerbank+ |
| Length (mm) | 103 | 120 |
| ←→ Width (mm) | 41 | 54 |
| → Height (mm) | 28 | 29 |
| Weight with Battery (g / oz) | 126 / 4.4 | 235 / 8.3 |
| (g / oz) | 55 / 1.9 | 164 / 5.8 |
| TECHNOLOGY | | |
| | 1x 21700 Li-ion Battery 3.7V | 2x 21700 Li-ion Battery 3.7V |
| Battery Capacity2 (Wh / mAh) | 16.65 / 4500 | 33.30 / 9000 |
| P Level | IP65 | IP65 |
| Rechargeable | Yes | Yes |
| Charging Time5 (min) | 140 | 240 |
| Energy Status | Battery Indicator, Charge Indicator, Low Battery Warning | Battery Indicator, Charge Indicator, Low Battery Warning |
| FEATURES | 6-IN-1 | 6-IN-1 |
| MATCHES | Powerbank with replaceable battery IP65 – water and dust protection Battery Charger (up to 30 % shorter charging time – compared to charging in a P7R CORE / WORK / SIGNATURE) Safe Battery Storage Double protection against short circuit (box and battery) Battery Charge Indicator H7R Core, P7R Core, P7R Signature, P9R Core LEP | Powerbank with replaceable battery IP65 – water and dust protection Battery Charger (up to 30 % shorter charging time – compared to charging in a P7R CORE / WORK / SIGNATURE) Safe Battery Storage Double protection against short circuit (box and battery) Battery Charge Indicator for both batteries H7R Core, P7R Core, P7R Signature, P9R Core LEP |
| PACKAGING | | |
| Item no. Box / GTIN | 502511 / 4058205026697 | 502127 / 4058205019286 |
| Content | 1 Rechargeable Battery, USB Cable (USB-A to USB-C) | 2 Rechargeable Batteries, USB Cable (USB-A to USB-C) |

¹⁻⁹ Information on page 84















Rethinking the Powerbank: Innovative 6-in-1 System

Flexible, sustainable, powerful – that distinguishes our new Flex series; the ideal addition for all outdoor activities. The rechargeable batteries of the new Ledlenser powerbanks can be removed at any time and are easy to swop out after being drained.

Therefore, the powerbanks can charge the 18650 respectively 21700 batteries used in compatible Ledlenser lights and in other electronic devices.






(USB Type-A to Type-C) Micro-USB cable included

FLEX-SERIES: EVEN MORE POWER ON THE GO



1 Rechargeable Battery, Micro-USB Cable 2 Rechargeable Batteries, Micro-USB Cable

| ☐ FOR 18650 BATTERIES | FLEX3 | FLEX7 |
|--------------------------------|--|--|
| TECHNICAL SPECS | Powerbank+ | Powerbank+ |
| ∠ Length (mm) | 109 | 109 |
| ←→ Width (mm) | 27 | 47 |
| Theight (mm) | 27 | 27 |
| Weight with Battery (g / oz) | 88 / 3.1 | 164 / 5.8 |
| Weight withoutBattery (g / oz) | 40 / 1.4 | 116 / 4.1 |
| TECHNOLOGY | | |
| ■ Battery | 1x 18650 Li-ion Battery 3.6V | 2x 18650 Li-ion Batteries 3.6V |
| Battery Capacity2 (Wh / mAh) | 12.34 / 3400 | 24.68 / 6800 |
| ্ৰ IP Level | IP65 | IP65 |
| Rechargeable | Yes | Yes |
| Charging Time5 (min) | 240 | 240 |
| Energy Status | Battery Indicator, Charge Indicator, Low Battery Warning | Battery Indicator, Charge Indicator, Low Battery Warning |
| FEATURES | 6-IN-1 | 6-IN-1 |
| TEATORES | 1. Powerbank with replaceable battery 2. IP65 – water and dust protection 3. Battery Charger (up to 30 % shorter charging time – compared to charging in a P6R CORE / WORK / SIGNATURE) 4. Safe Battery Storage 5. Double protection against short circuit (box and battery) 6. Battery Charge Indicator | 1. Powerbank with replaceable battery 2. IP65 – water and dust protection 3. Battery Charger (up to 30 % shorter charging time – compared to charging in a P6R CORE / WORK / SIGNATURE) 4. Safe Battery Storage 5. Double protection against short circuit (box and battery) 6. Battery Charge Indicator for both batteries |
| MATCHES | | |
| | P6R Core, P6R Signature | P6R Core, P6R Signature |
| PACKAGING | | |
| Itemno. Box/GTIN | 502126 / 4058205019255 | 502125 / 4058205019224 |











Contents Box

ACCESSORIES FLASHLIGHTS

C = Core S = Signature

| ARTNR.MODELL | | P2R C | P3 C | P4 C | P4R C | P5 C | P5R C | P6 C |
|--------------|---|-------|------|------|-------|-------------|-------|------|
| 0337 | Pouch Type D | • | • | | | • | | |
| 502249 | Lamp Adapter Type B | | | | | | • | |
| 0362 | Universal Mounting System | | | | | | | • |
| 501025 | Remote Switch Type E | | | | | | | • |
| 0380 | USB Car Charger | • | | | • | | • | |
| 502265 | Magnetic Charging Cable Type A | | | | | | • | |
| 502259 | Charging Station Type A | | | | | | • | |
| 502596 | Li-Ion direct USB rech, Battery 3.6 V / 880 mAh | | | | | | • | |
| 500985 | 14500 Li-Ion rechargeable battery 750 mAh | | | | | • | • | |





| ARTNR | MODELL | P17R C | P18R S |
|--------|--------------------------------|--------|---------------|
| 0042 | Signal Cone 53mm Orange | • | |
| 0380 | USB Car Charger | | • |
| 502265 | Magnetic Charging Cable Type A | | • |



Diverse Item no. Signal Cone

The plastic plug-in attachment quickly transforms a flashlight into a versatile red signal light at any time, e. g. for signal light



| ARTN | R.MODELL | P6R C | P7 C | P7R C | P6R C | CP6R <mark>S</mark> | P7R <mark>5</mark> | P9R C LE |
|--------|---|-------|------|-------|-------|---------------------|--------------------|----------|
| 0333 | Pouch Type A | | • | | | | | |
| 0342 | Pouch Type G | | | • | • | • | • | |
| 502269 | Leather Pouch Type D | | | • | | | • | |
| 0323 | Tactical Professional Holster Type B | | • | • | | | • | • |
| 502250 | Lamp Adapter Type C | • | | | | | | |
| 502251 | Lamp Adapter Type D | | | • | • | | • | • |
| 0317 | Intelligent Clip Type C | | • | | | | | |
| 0362 | Universal Mounting System | • | • | • | • | | • | • |
| 501033 | Magnetic Mount | • | • | • | • | • | • | • |
| 502237 | Signal Cone 35.1mm Orange | • | | • | | • | • | |
| 0040 | Signal Cone 37mm Orange | | • | | | | | |
| 502238 | Color Filter Set 35.1mm | • | | • | | • | • | |
| 502729 | Remote Switch Type G | | | | • | | | |
| 0380 | USB Car Charger | • | | • | • | • | • | • |
| 502265 | Magnetic Charging Cable Type A | • | | • | | • | • | • |
| 502260 | Charging Station Type B | • | | • | | • | • | |
| 502262 | 21700 Li-ion Rechargeable Battery 4800mAh | | | • | | | • | • |
| 502595 | Li-Ion direct USB rech. Bat. 3,6 V / 2500 mAh | • | | | • | • | | |
| 502126 | Powerbank Flex3 | • | | | • | • | | |
| 502125 | Powerbank Flex7 | • | | | • | • | | |
| 502511 | Powerbank Flex5 | | | • | | | • | • |
| 502127 | Powerbank Flex10 | | | • | | | • | • |
| 501001 | Li-Ion rechargeable Battery 3,6 V / 3000 mAh | • | | | • | • | | |



Item no. 502262 Charging Station Professional charging station incl. magnetic charging cable, compatible with 5 Station Charging Panel











Four high quality color filters: Red maintains night vision ability. Green and red are suitable for animal observation, among other things. Yellow improves visibility in fog. Blue improves the visibility of liquids



Item no. 0362 **Universal Mounting System**

This universal mounting fixes flashlights with a diameter of 25-34 mm securely to tripods, rods and tubes in next to no time. The light and fixation are aligned in parallel




Stable universal fastening to

cylindrical objects

ACCESSORIES HEADLAMPS

C = Core S = Signature

| ARTN | R.MODELL | HF4R C | HF6R C | HF8R C / HF8R C RGB | H5 C | H5R C | H7R C | H15R C | H19R C |
|--------|---------------------------------------|-----------|-----------|---------------------------|------|-------|-------|-----------|-----------|
| 0332 | Pouch Type H Belt Clip Type A Helmet | • | • | • | • | • | | | |
| 502253 | Connecting Kit Type H Helmet Band | | | | | | | • | • |
| 502314 | Fixing Clip Type A Universal Mounting | • | • | • | • | • | • | • | • |
| 502313 | Bracket Type E Transparent Silicone | | | | • | • | • | • | • |
| 502256 | | • | • | • | • | • | • | • | • |
| 502451 | Headband Type A | | | | • | • | • | • | • |
| 502469 | Headband+Overheadband Core | | | | • | • | • | • | • |
| 502311 | Bluetooth®8 Remote Control Type A | | | • | | | | | |
| 502265 | Magnetic Charging Cable Type A | • | • | • | | • | • | • | • |
| 502312 | Extension Cable Type C 21700 Li-ion | | | | | | | • | • |
| 502262 | •• | | | | | | • | | |
| 502411 | Recharge. Battery 4800mAh | | | | | | | • | • |
| 502511 | Bluetooth®8 2x 21700 Batterybox | | | | | | • | | |
| 502127 | Powerbank Flex5 Powerbank Flex10 2x | | | | | | • | | |
| 502310 | 21700 Li-Ion Recharge. Battery Pack | | | | | | | • | • |
| 502929 | USB-C Adapter 20W | • | • | • | | | | | |







Item no. 502314

Helmet Connecting

Kit Type H

Stable helmet holder
system for a wide variety
of helmet models





Item no. 502256

Universal Mounting Bracket
Stable universal fastening
for rods





Practical extension cable (120 cm) that is plugged in between the lamp head and the battery box - so the battery can easily be stowed in the backpack




Item no. 502265

Magnetic Charging Cable

Magnetic charging cable with standard USB-A connector

ACCESSORIES LANTERNS

| ART NR. | MODELL | ML4/W | LML6/W | IML6 C \ |
|------------|---|-------|--------|----------|
| 502311 | Bluetooth®8 Remote Control Type A | | | • |
| 502265 | Magnetic Charging Cable Type A | | | • |
| 502595 | Li-lon direct USB rech. Battery 3.6 V / 2500 mAh | | • | • |
| 502596 | , , | • | | |
| 500985 | Li-Ion direct USB rech. Battery 3,6 V / 880 mAh 14500 | • | | |
| 502126 | Li-Ion rechargeable battery 750 mAh Powerbank | | • | • |
| 502125 | Flex3 Powerbank Flex7 14500 | | • | • |
| 500986 | Li-lon battery 750 mAh & external charger | • | | |
| 501001 | Li-Ion rechargeable Battery 3,6 V / 3000 mAh | | • | • |



TECHNOLOGIES, ABOUT US, WARRANTY AND MORE







LEDLENSER TECHNOLOGY ABC



LASER EXCITED PHOSPHOR TECHNOLOGY



gy. This is how it works: Blue laser light is directed at a phosphor-coated plate and transformed into white light which then travels through two lenses, resulting in a white light that is highly focused and has an extreme range. You can use it for Morse code or on search and rescue missions.





ACTIVE COOLING TECHNOLOGY

Highluminosity requires special measures. A powerful fan actively cools down the high-end LED and allows maximum light output over long periods of time – while remaining consistently energy-efficient.





ADAPTIVE LIGHT BEAM


Our Adaptive Light Beamtechnology dims and focuses automatically. This way, the light is adapted to changing environments and obstacles; from uneven forest ground and wet sidewalks to narrow machine compartments – without manual control. The system detects blinding reflections as well as overall light conditions and controls all light sources separately. This does not only result in an ideal illumination and focusing, but it also enables completely hands-free use, with an extended battery runtime.





ADVANCED FOCUS SYSTEM (AFS)


Galileo swore by the power of lenses; Newton by the power of reflectors. We have simply combined the two Technologies – only better than anyone before. The result: our patented Advanced Focus System (AFS), which allows a seamless transition from homogeneous low beam to sharply focused high beam.





COOLING TECHNOLOGY

Cooling Technology (CT) ensures your head stays cool even when your light is at maximum power. Our CT products reduce LED heat to the optimal level by means of the intelligent use of cooling elements. This technology is also used to cool computer chips and ensures highly efficient use of energy, increased illuminating power, and especially long-lasting LEDs.





DIGITAL ADVANCED FOCUS SYSTEM

Our patent-pending Digital Advanced Focus System (dAFS) allows a virtually seamless transition from homogeneous floodlight to focused spotlight. Its efficiency delights even experts. The technology enables a slim design, ideal lighting for different ranges and permanent peripheral vision.





DUAL POWER SOURCE

Our Dual PowerSource allows you to use the full performance of your Ledlenser at any time – no matter what power source you have available. This technology recognizes the power source and you can therefore. You can therefore choose between the rechargeable Ledlenser battery or a disposable battery. Extremely practical for long trips without a power point.





EMERGENCY LIGHT

This feature turns your flashlight into an emergency light: If the power goes out while your Ledlenser is on the charging base, it will automatically turn on. So the light helps you find your way around, e. g. to the breaker panel.





EXTREME SEARCH BEAM

Our Extreme Search Beam consists of several powerful LEDs and a unique optical system for extreme long-range vision. The light is sharply focused to prevent glare at close range. The ultimate light beam for long-range vision.





FLEX SEALING TECHNOLOGY


Theinnovative Flex Sealing Technology ensures that the electronic parts of the lamp head are completely sealed off, to protect against the penetration of water and dust. This flexible system maintains the seal, even when the Advanced Focus System is used. The focus can even be used underwater.



(

RAPID FOCUS

When focusing or defocusing the flashlight or headlamp, the reflector lens moves in relation to the LED. To ensure this process is as quick and ergonomic as possible we developed Rapid Focus: a single-hand mechanism that allows the light beam to be adjusted as fast as lightning.





FLOATING CHARGE SYSTEM

Grab-and-go wireless charging. The Floating Charge System is a wall-mounted magnetic charging system, getting the light ready to go with a simple flick of the wrist. It also offers USB charging with an adapter system that can be plugged into standard outlets or car lighters.





SAFETY YTRION CELL

Ledlenser's Safety YtrionCell is a special lithium iron phosphate battery with unique properties: The technology combines high energy density with superior durability and safety, even in rough use and adverse storage conditions.





FUSION BEAM


Bycombining different LEDs and lenses, lights with Fusion Beam have a unique, application-optimized illumination. This simultaneously enables a homogenous close-up wide flood beam and sharply focused long-distance beam. The intensity of the flood and spot beams can be individually adjusted thanks to independent controls for each light source.





SMART LIGHT TECHNOLOGY (SLT)

This innovation turns a Ledlenser into your personal lighting tool:
A micro-controller allows individual ranges of functions to be
programmed to different touch and switch combinations. That
way, you always have the perfect light mode at hand.








MAGNETIC CHARGE SYSTEM

With the Magnetic Charge System, the charging cable can quickly and easily be attached to the light. The connection for charging the battery is made via magnetic contacts. When the contacts approach each other, the charging cable automatically pairs with the light. The connection is automatically released under load.





TEMPERATURE CONTROL

Our lights stay cool, even when they work hard. Thanks to the intelligent and fully automated temperature control, a Ledlenser never gets too hot, no matter how much it is used. This protects you from burns and the LED from overheating.





MULTI-CORE OPTICS

Multi-Core Opticsharness and direct the light emitted from extremely powerful, next-generation LEDs. The special faceted lens tames and directs the light, resulting in a homogeneous beam and aesthetic illumination.





X-LENS TECHNOLOGY

This technology is an enhancement of the Advanced Focus System. It can merge virtually any number of reflector lenses and synchronizes their individual light beams into a perfect beam, resulting in a high-grade, homogeneous floodlight in unfocused mode and our most sharply focused high beam to date.



¹⁻⁹ Information on page 84

LEDLENSER

WHAT SETS US APART

- One of the global market leaders in portable lights. That includes: Flashlights, headlamps, work lights, floodlights, lanterns, EX-protected lights
- > German Engineering & Design": In-house development, production and quality assurance
- > Inventor of the trendsetting and patented³ Advanced Focus System
- > 7-year warranty⁴ for most products in connection with online registration
- More than 100 industrial property rights as well as more than 200 awards and prizes for our products
- > More than 650 employees worldwide
- Company-owned offices in Germany, China, USA, Japan, Denmark, United Kingdom, France, Italy and Switzerland
- > Worldwide collaboration with more than 40 master distributors

To ensure that our bright ideas see the light of day, we clearly divided up our tasks: "Engineered in Germany, produced in China". Our production expertise is concentrated at our location in Yangjiang, Guangdong. Every product is manufactured and tested here; from prototype to mass production.

The checklist for quality control includes 24 tests: Endurance, extreme temperatures, water, salt, impact, pressure and more - inspected and tested until the products have overcome all obstacles and meet our quality standards. Furthermore, it is important to us to take responsibility for our employees in China. We do this for example by building company housing and through our involvement in social and intercultural projects.







1-9 Information on page 8

MORE THAN 20 YEARS OF EXPERTISE IN LIGHTING SOLUTIONS

When the two brothers Harald and Rainer Opolka from Solingen started out, they really didn't have much more than a garage, an old Atari computer, a set of tools, a drawing pad and around 1000 Deutschmarks of seed capital. Today, the former garage company of both the Ledlenser founders is an internationally operating company and one of the global market leaders in portable lights. The German Ledlenser brand conquered the flashlight market in the year 2000. The approach of equipping a flashlight with an LED instead of a bulb as a light source was absolutely visionary at that point in time. Millions of the "V8 Photon Pump" were sold worldwide and it constituted a new era of portable light – the "P7" achieved the same thing several years later.

To meet our objective as an LED pioneer, we are still using this technological advantage today in the development of new products – particularly in times during which LED lighting has become the norm in so many places and genuine quality is becoming harder and harder to recognize. At the same time, our premise "German Engineering & Design" has guided us from day one and justifies our unique commitment to quality. Ledlenser products give users worldwide the freedom of doing their jobs to the best of their ability or pursuing their passion with devotion – with the best possible light on their side.

LEDLENSER GUARANTEED QUALITY







ZERTIFIZIERT

Management System ISO 9001:2015 ISO 14001:2015 ISO 50001:2018

www.tuv.com ID 9108640713

QUALITY

"German Engineering & Design" - this statement stands for the highest development and production standards in regard to technology, design, materials and workmanship. We hold more than 100 industrial property rights. These include patents, utility models and designs. We are proud of having received various design awards for our products.

WARRANTY

Since weareconfident in the quality of our lights, we grant a seven-year warranty on nearly all products in connection with online registration. All original Ledlenser products covered by our warranty include a product registration card. To register, simply scan the QR code with a smartphone or enter the indicated URL on your laptop or PC.

ISO CERTIFICATION

We meet therequirementsofthe ISO 9001, ISO 14001 and ISO 50001 standards and are certified by $T\ddot{U}V$ Rheinland.

Quality management: DIN EN ISO 9001:2015

Our systematic quality management ensures a consistently high quality of our products and services. Clearly defined and comprehensible processes enable us to meet our customers' expectations consistently and professionally. We also meet the standard requirements at our Chinese location.

Environmental management: DIN EN ISO 14001:2015 Our company has defined an internal environmental policy and precise environmental objectives. Here, the focus is on the establishment and realization of an environmental management system, to ensure continuous improve- ments – e. g. in regard to CO_2 emissions, the use of resources and other environmental factors.

Energy management: DIN EN ISO 50001:2018

We operate energy management geared towards sustainability. This includes measures to reduce the consumption of energy such as electricity, gas and fuel as well as specific risk prevention.

¹⁻⁹ Information on page 84

NOTES

The information pertaining to package contents, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change package contents, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and misprints excepted.

1) Measurements according to ANSI FL1 on the respective setting. If no setting is explicitly indicated, the values refer to luminous flux (Lumen/lm) and beam distance (meters/m) on the highest setting and to the run time (hours/h) on the lowest setting. If the light is equipped with color LED(s), the measurements indicated apply to white light or white LED. A boost function (if applicable) can be used several times, but only for short periods of time. If the light has different energy modes, measurement is based on "energy saving mode."

2) Calculated capacity value in watt-hours (Wh) or milliampere hours (mAh). This applies to the delivery state of the battery/ies inside the respective item, or for lights with rechargeable battery/ ies, to the rechargeable battery/ies inside the product when fully 8) The Bluetooth® word mark and logos are registered tradecharged.

3) EP Patent 1880139; US Patent 7,461,960

4) Two year warranty from the date of purchase, or seven years with online registration through our website. The warranty applies worldwide; legal warranty rights also apply. It covers defects in material and manufacture. Battery packs are guaranteed to work correctly for 24 months. This warranty does not cover products in the "Solidline" series, the LiteWallet®, the Powercase, the Batterybox7, the Kidled-Series also the Ledlenser K-Serie (except K3),, as well as defective batteries, holsters, pouches, remote switches, color filters, imprints and surface coatings. The warrantor is Ledlenser GmbH & Co. KG, Kronenstr. 5-7, 42699 Solingen, Germany. For more information visit ledlenser. com/warranty

5) The average charging time of the batteries in the delivery state in minutes may vary depending on the power supply unit used.

6) Additional talk time using the example of an iPhone X when charging with the fully charged batteries contained in the content of the article in question.

7) EP Patent 3376097

marks owned by Bluetooth SIG, Inc. and any use of these by Ledlenser GmbH & Co. KG is under license

9) EP Patent 3717826

You can find our terms and conditions at www.ledlenser.com

Ledlenser GmbH & Co. KG Kronenstraße 5–7, 42699 Solingen, Germany Sales tax ID: DE815242425, Local Court Wuppertal, HRA 23078 Personally liable partner: Ledlenser Beteiligungs GmbH Headquarters: Solingen, Germany Local Court Wuppertal, HRB 24774 Executive Director: Michael Reuter (CEO), Kai Milewski (CFO)

-LEDLENSER WE'RE LOOKING FORWARD TO HEARING FROM YOU

We are always looking for ways to improve our support for you and your customers. We greatly appreciate any feedback you have on how we can build the Ledlenser brand together.

CONTACT SALES GERMANY vertrieb@ledlenser.com

CONTACT TECHNICAL SUPPORT

For uncomplicated and fast processing, please contact our Consumer Care Team for all services, product, warranty and goodwill questions.

Customers from Germany can reach us by e-mail: support@ledlenser.com Customers from Belgium, the Netherlands and Luxembourg can reach us by e-mail:

info.bnl@ledlenser.com

Customers from Austria can reach us by e-mail: support@ledlenser.at Customers from Switzerland can reach us by e-mail: office@ledlenser.ch









